




MISTA RANDOM

DESCRIPTION: Paver **TEXTURE:** Multi-textured

PALLET OVERVIEW



Permeable pavers allow for storm water drainage and manage excess runoff. The use of permeable pavers also facilitates LEED® certification easier to obtain.

NOTES

See page 62 to 64 for more technical information. When used in a permeable pavement application, see page 33 and 101 for more technical information.

See page 30 for more information about applications.

JOINT WIDTH: 3/16" TO 9/16" (4 TO 14 mm)


% OF SURFACE OPENING: 6.3%

INFILTRATION RATE: 610 in./hr
(15 505 mm/hr)


| Specifications per pallet | Imperial | Metric |
|---------------------------|------------------------------|----------------------|
| Cubing | 116.20 ft² | 10.80 m ² |
| Approx. Weight | 3 356 lbs | 1 522 kg |
| Number of rows | 10 | |
| Coverage per row | 11.62 ft ² | 1.08 m ² |
| Linear coverage per row | 17.71 lin. ft | 5.40 lin. m |

| | Unit dimensions | in | mm | Units/pallet |
|----------|-----------------|----------|-----|--------------|
| A | | | | |
| | Height | 2 9/16 | 65 | 80 units |
| | Width | 7 7/8 | 200 | |
| | Length | 3 15/16 | 100 | |
| B | | | | |
| | Height | 2 9/16 | 65 | 100 units |
| | Width | 7 7/8 | 200 | |
| | Length | 7 7/8 | 200 | |
| C | | | | |
| | Height | 2 9/16 | 65 | 90 units |
| | Width | 7 7/8 | 200 | |
| | Length | 11 13/16 | 300 | |


04 | Modular pattern



05 | Modular pattern



06 | Linear pattern



Patterns are for design inspiration only. The installer is responsible to calculate & purchase the correct amount of material.

Chestnut Brown



Sandlewood



Champlain Grey



Shale Grey

